



## Siena Nylon Carpet Specifications: Escape

Style Name	<b>ESCAPE</b>
Style Number	71
<b>SPECIFICATIONS</b>	
Construction	Tip-Sheared Loop Pattern
Yarn Content	Avalar® SD Nylon
Odor Reduction	Puralex®
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	11.3 S.P.I. (44.6/10 cm.)
Yarn Weight Tufted	45 oz./yd.2 (1,525 g./m.2)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66 m.)
Pattern Repeat	.20" W x 00" L (.51 cm. x 00 cm.)
Tile Size	N/A
<b>PERFORMANCE</b>	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP7078
<b>WARRANTIES</b>	
Nexterra®	N/A
Wear	10 Year Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
<b>ADDITIONAL INFORMATION</b>	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
Sustainability	N/A
<b>RECOMMENDED INSTALLATION(S)</b>	
	Fuzzy Side Up

**1.888.977.4362**

**WWW.SIENAUSA.COM**



## Siena Nylon Carpet Specifications: Escape

Style Name	<b>ESCAPE TILE</b>
Style Number	71T
<b>SPECIFICATIONS</b>	
Construction	Tip-Sheared Loop Pattern
Yarn Content	Avalar® SD Nylon
Odor Reduction	Puralex®
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	10 S.P.I. (39.4/10 cm.)
Yarn Weight Tufted	32 oz./yd.2 (1,085 g./m.2)
Primary Backing	Non-Woven
Secondary Backing	Nexus® tile backing
Width	N/A
Pattern Repeat	N/A
Tile Size	24" W x 24" L (61 cm. x 61 cm.)
<b>PERFORMANCE</b>	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP8595
<b>WARRANTIES</b>	
Nexus®	Lifetime Limited*
Wear	Lifetime Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
<b>ADDITIONAL INFORMATION</b>	
Backing Options	N/A
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
Sustainability	Certification ANSI/NSF 140 Platinum
<b>RECOMMENDED INSTALLATION(S)</b>	
	1/4 Turn, Monolithic

**1.888.977.4362**

**WWW.SIENAUSA.COM**



## Siena Nylon Carpet Specifications: Escape

Style Name	<b>ESCAPE TRIMLINE</b>
Style Number	71L
<b>SPECIFICATIONS</b>	
Construction	Tip-Sheared Loop Pattern
Yarn Content	Solution Dyed Nylon
Dye Method	Solution
Machine Gauge	1/10 in. (39.4 col./10 cm.)
Stitch Count	10 S.P.I. (39.4/10 cm.)
Yarn Weight Tufted	32 oz./yd.2 (1,085 g./m.2)
Primary Backing	Woven Polypropylene
Secondary Backing	Woven Polypropylene
Recycled Content	N/A
Width	12 Feet (3.66 m.)
Pattern Repeat	.20" W x 00" L (.51 cm. x 00 cm.)
Tile Size	N/A
<b>PERFORMANCE</b>	
Static Control	Less Than 3.5 K.V. Step
Flame Resistance	Passes (DOC FF-1-70)
Flooring Radiant Panel	Class 1 (ASTM E-648)
Smoke Density	Less Than 450 (ASTM E-662)
Soil Resistance	Commercial Anti-Soil Protection
Stain Resistance	Commercial Stain Protection
CRI Green Label Plus	Certification# GLP7078
<b>WARRANTIES</b>	
Nexterra®	N/A
Wear	10 Year Limited*
Stain, Static and Colorfastness	Lifetime Limited*
	*See website for full warranties
<b>ADDITIONAL INFORMATION</b>	
Backing Options	Contact Sales Representative
Custom Colors	Contact Sales Representative
Environmental	Proud member of the EPA's Green Power Partnership
Sustainability	N/A

**1.888.977.4362**

**WWW.SIENAUSA.COM**